

Teleswitch TSE10 or TSE10-D



Very easy: Power socket controlled by phone

Teleswitch TSE10 e TSE10-D

Semplicissimo: Presa attivabile su chiamata telefonica



Phone call / Telefonata
—————▶



ECOLINE

Features:

- Switch the power socket by a telephone call, 10A/230VAC
- Control LED for status information
- 1 power socket (CH or D)
- 1 analogue telephone connection
- ON / OFF switching
- Count down timer integrated (1 to 99 h)
- Manual override switch

The product comes with:

- User manual DE, FR, IT, EN
- Telephone cable 3.0m including Plug

Caratteristiche:

- 1 presa elettrica telecomandata da chiamata telefonica, 10A/230VAC
- 2 LED per la qualità del segnale e lo stato del Teleswitch
- 1 presa elettrica a ritorno del Teleswitch
- 1 Cavo e connettore per l'allacciamento alla rete del telefono analogico
- Attivazione ON / OFF (EIN / AUS)
- Countdown-Timer per l'attivazione 1-99 ore
- Pulsante per la commutazione manuale sul Teleswitch

Volume di consegna:

- Manuale istruzioni DE, FR, IT, EN
- Cavo telefonico lunghezza 3.0m e connettore

Elbro-No	E-No	Max. Switching capacity Portata massima del contatto	Power supply Tensione di esercizio	Operating temperature Temperatura di esercizio	Dimensions Dimensioni
Teleswitch CH Plug / Presa					
TSE10	954 876 166	max. 10 A, 230VAC	230VAC	-5 – +45 °C	68 x 135 x 55 mm (B/H/T) (L/H/P)
Teleswitch German Plug / Presa					
TSE10-D		max. 10 A, 230VAC	230VAC	-5 – +45 °C	68 x 135 x 55 mm (B/H/T) (L/H/P)