



Components

COU-90,010-61 966 702 766

Jack ITplus® RJ45 Cat.6A 10G, unshielded

For setting up Class D and E transmission links with up to 4 plug-in connections. Fulfils the requirements of ISO/IEC 11801 (2), EN 50173-1 (2), IEC 60603-7 and TIA/EIA568B.2-10 draft Cat.6A. For wire diameter AWG23-26. Parallel connection in pairs without crossing of pair in accordance with EIA/TIA 568A/B. Strain relief of cable by means of included cable ties, single strain relief of wires, >20 overplugging cycles. Gold-plated contacts on nickel, for >1000 insertion/withdrawal cycles. With integrated and captive dust protection cap. For Keystone brackets, fast and easy installation.



COS-90 010-61 966 702 866

Jack ITplus® RJ45 Cat.6A 10G, shielded

For setting up Class D and E (A) transmission links with up to 4 plug-in connections. Fulfils the requirements of ISO/IEC 11801 (2), EN 50173-1 (2), IEC 60603-7 and TIA/EIA568B.2-10 draft Cat.6A. For wire diameter AWG23-26. Parallel connection in pairs without crossing of pair in accordance with EIA/TIA 568A/B. Strain relief of cable by means of included cable ties, single strain relief of wires, >20 overplugging cycles. Gold-plated contacts on nickel, for >1,000 insertion/withdrawal cycles. With integrated and captive dust protection cap. For Keystone brackets, fast and easy installation.



SOH-12 101 977 801 048

Jack ITplus® RJ11 screw connection

For connecting cables (U72) for ADSL, ISDN and POTS. Meets requirements of IEC 60512-7. Screw connection with tension spring terminals enables parallel connection of wire diameters 0.5-1 mm² AWG22-27. 4 contacts 2,3,4,5 are reserved (USOC RJ11). Tension relief by means of cable ties, >20 overplugging cycles. Gold-plated contacts on nickel, for >1000 insertion/withdrawal cycles. With integrated and captive dust protection cap. For Keystone brackets, fast and easy installation.



IEU-11 100 977 830 098

Coupling ITplus® RJ45 Cat.6, unshielded

For setting up distribution fields and workplace boxes with two-sided RJ45 connection. Fulfils Cat.6/Class E Permanent Link and Channel requirements of ISO/IEC 11801, EN 50173, IEC 60603-7 and TIA/EIA 568B.2. Gold-plated contacts on nickel, for >750 insertion/withdrawal cycles. For Keystone brackets, fast and easy installation.



IES-11,100 977 800 098

Coupling ITplus® RJ45 Cat.6, shielded

For setting up distribution fields and workplace boxes with two-sided RJ45 connection. Fulfils Cat.6/Class E Permanent Link and Channel requirements of ISO/IEC 11801, EN 50173, IEC 60603-7 and TIA/EIA 568B.2. Gold-plated contacts on nickel, for >750 insertion/withdrawal cycles. Die cast housing with earthing contact. For Keystone brackets, fast and easy installation.



COU-93,001-61 966 733 808

Dummy insert ITplus®

Cover element for Keystone reserve slots, white.

